

POWERED BY **BAFANG**



Actual products may differ from image shown.

## FRAMESET

Frame	6061-T6 Alloy, Hydroformed M12x138mm, Bolt-On
Fork	6061-T6 Alloy, 9x100mm, QR

## WHEELS

Rims	27.5" EVO Disc Wide double wall, 36H, 35mm inner width
Front Hub	9x100mm QR, 6-Bolt
Rear Hub	Bafang G020 Hub, M12x138mm, 6-Bolt, HG Freehub
Spokes	F:14G / R:13G Stainless Steel
Tires	Vee Rubber Speedster, 27.5 x 2.8", E-Bike Ready, 72TPI

## POWER ASSISTANCE

Motor Unit	Bafang G020 rear hub motor, 500W, 60Nm, 36V
Battery	Downtube semi integrated, 522Wh, (36V, 14.5Ah), Lockable
Sensor	Speed sensor, BB mount, 12 pulse

## DRIVETRAIN

Shifter	Shimano SL-M3000-R, 9 Speed, Rapidfire
Rear Derailleur	Shimano RD-T3000-SGS
Crank Set	Forged alloy, 170mm, 42T w/Chaincover
Freewheel/Cassette	Shimano CS-HG400-9, 11-36T, 9 Speed
Chain	KMC E9 EPT Anti Rust

## COMPONENTS

Saddle	Megasoft
Seat Post	EVO forged alloy, micro-adjustable, 30.9mm
Handlebar	EVO City, 25.4mm
Stem	EVO alloy, Threaded, Extension 60mm, 25.4mm
Grips	Kraton rubber, Lock-on, 135mm
Brakes	Shimano MT200, Hydraulic disc brake, 160mm rotor
Pedals	One-piece non-slip composite platform
Headset	ZeroStack Threadless, 44/28.6   44/30
Bottom Bracket	Sealed cartridge bearings, 73mm

## ACCESSORIES

Front and rear LED light, bell, bolt-on rear kickstand, battery charger, tool kit



## GEOMETRY

SIZE	SM	ML
Seat Tube - mm	370	450
Seat Tube Angle	74°	70°
Top Tube - Effective - mm	602	620
Head Tube - mm	165	180
Head Tube Angle	69°	69°
Chain Stay - mm	480	480
Wheelbase - mm	1165	1165

## DRIVE UNIT

- Bafang G020 Rear hub motor
- Nominal power: 500W / 60 Nm
- Max assist speed: 20 mph / 32 kmh

## BATTERY

- Bafang 36V Li-Ion
- Capacity: 522Wh
- Battery Charger included

## HMI

- Bafang C11 Compact LCD Computer
- Handlebar left side mounted
- Cycle Computer functions
- Walk Assist function

PRODUCT #	DESCRIPTION		
921174-01	SM	ML	Denim