

POWERED BY **BAFANG**



Actual products may differ from image shown.

## FRAMESET

Frame	6061-T6 Alloy, Hydroformed M12x175mm, Bolt-On
Fork	6061-T6 Alloy, Tapered, 15x150mm, Thru-Axle QR

## WHEELS

Rims	27.5" EVO Disc Wide double wall, 36H, 45mm inner width
Front Hub	15x150mm QR Thru-Axle, 6-Bolt
Rear Hub	Bafang G060 Hub Motor, M12x175mm, 6-Bolt, HG Freehub
Spokes	F:14G / R:13G Stainless Steel
Tires	Vee Rubber Snow Avalanche, 27.5 x 4.5", 72TPI

## POWER ASSISTANCE

Motor Unit	Bafang G060 rear hub motor, 500W, 80Nm, 36V
Battery	Downtube semi integrated, 576Wh (36V, 16Ah), Lockable
Sensor	Speed sensor, BB mount, 12 pulse

## DRIVETRAIN

Shifter	Shimano SL-M3000-R, 9 Speed, Rapidfire
Rear Derailleur	Shimano RD-M3100-SGS
Crank Set	Forged alloy, Narrow-Wide, 34T, 170mm
Freewheel/Cassette	Shimano CS-HG400-9, 11-36T, 9 Speed
Chain	KMC E9 EPT Anti Rust

## COMPONENTS

Saddle	Megasoft
Seat Post	EVO forged alloy, micro-adjustable, 30.9mm
Handlebar	EVO Riser, DB alloy, 31.8mm
Stem	EVO 3D forged alloy, Threadless, Extension 60mm, 31.8mm
Grips	Kraton rubber, Lock-on, 135mm
Brakes	Shimano MT200, Hydraulic disc brake, 160mm rotor
Pedals	One-piece non-slip composite platform
Headset	Integrated Threadless, Taper 42/28.6   52.2/39.8
Bottom Bracket	Sealed cartridge bearings, 100mm

## ACCESSORIES

Bell, Bolt-on rear kickstand, battery charger, tool kit



## GEOMETRY

SIZE	SM	ML
Seat Tube - mm	405	470
Seat Tube Angle	73.5°	73.5°
Top Tube - Effective - mm	570	615
Head Tube - mm	115	125
Head Tube Angle	66.5°	66.5°
Chain Stay - mm	510	510
Wheelbase - mm	1205	1250

## DRIVE UNIT

- Bafang G060 Rear hub motor
- Nominal power: 500W / 80Nm
- Max assist speed: 20 mph / 32 kmh

## BATTERY

- Bafang 36V Li-Ion
- Capacity: 576Wh
- Battery Charger included

## HMI

- Bafang C10 3.5" LCD Computer
- Handlebar left side mounted
- Cycle Computer functions
- Walk Assist function

PRODUCT #	DESCRIPTION		
921175-01	SM	ML	Red